PACE 417 \* RCVD AT 41312011 8:10:50 AM [Eastern Daylight Time] \* SVR:W-PTOFAX-00112 \* DNIS:2738300 \* CSID:+41213736112 \* DURATION (mm-ss):01-03

## **GIORDANO**

Appl. No 10/597,861

## **AMENDMENTS TO THE CLAIMS:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

- 1. (Canceled)
- 2. (Canceled)
- 3. (Canceled)
- 4. (Canceled)
- 5. (Canceled)
- 6. (Canceled)
- 7. (Canceled)
- 8. (Canceled)
- 9. (Canceled)
- 10. (Canceled)
- 11. (Canceled)
- 12. (Canceled)
- 13.(Canceled)
- 14. (Canceled)
- 15. (New) A safety device for a bracelet including a system for adjusting the circumferential length of the bracelet, wherein the system comprises:
  - first and second curvilinear elongated elements, each having a slot and a plurality of notches
  - a clasp comprising a third curvilinear elongated element having a set of grooves, wherein the grooves receive one of the first or second elongated elements for slidably gliding the elements relative to one another, and a fourth curvilinear elongated element
  - a button slidably secured in each slot of said first and second curvilinear elongated elements to slidably secure said first and second curvilinear elongated elements together

PAGE 517 \* RCVD AT 41232011 8:10:50 AM [Eastern Daylight Time] \* 5VR:W-PTOFAX-00112 \* DNIS:2738300 \* CSID:+41213214412 \* DURATION (mm-ss):01-03

## Appl. No 10/597,861

 a set of stop reliefs are provided within said grooves for limiting the sliding motion of the first and second curvilinear elongated elements

wherein the third and fourth curvilinear elongated elements are engaged with one another after the safety device is adjusted to a desired position in order to lock the device in that desired position.